

Product Spec Sheet



VT-6436CCT 36W LED BACKLIT PANEL 595x595MM 3 SWITCH CCT 120LM/W



FEATURES

- TP(a) rated Diffuser to meet fire safety standards
- CCT Changeable with DIP Switch
- Highly efficient LIFUD Driver
- Powerful LED light source with lumen efficeincy of 120LM/W
- IP40 for Panel and IP20 for Driver
- Flicker Free and No UV Radiation
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, kitchens etc

TECHNICAL INFORMATION

Output Voltage:	DC:33-40V		
On Sale:	No		
Color Temperature:	3IN1		
Model:	VT-6436CCT		
Watts:	36		
Lumens:	4320		
Input Power:	AC:220-240V, 50Hz		
Unit Color:	White		
Color for Web:	3IN1		
Body Type:	Aluminium+TPA(PC)		
Dimension:	595x595x34mm		
Operation Temperature:	-20°C to +40°C		
Instant Start:	0-100% in < 1s		
On/Off Cycles:	>15000		
PF:	>0.9		
LED Chip Type:	SMD		
Beam Angle:	110°		
CRI:	>80		
Energy Rating Label:	E (2021)		
IP Rating:	IP40		
Long Life:	30,000 Hours		
Driver Brand:	LIFUD		
lumens per watt:	120		
EMC Certificate:	Check the certificate		



LVD Certificate:

ROHS Certificate:







LISTING DETAILS

SKU:	6972 VT-6436CCT	
Model:		
EAN:	3800157698269	

Commodity	Code
-----------	------

PACKAGING

Gross Weight (Kgs):	2.43		
Unit CBM:	0.019489		
Dimension:	595x595x34mm		

MASTER BOX PACKAGING

Check the certificate

Check the certificate

ox Qty:	6
ty Per Pallet:	30
ength (Box) mm:	628
/idth (Box) mm:	27
eight (Box) mm:	665