



Disco EVO

Part of the Bulkheads product category



Model	Disco EVO 2 XPRESS
Code	ADIS2/2
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	8 - 16W
Operating Temp	-20°C - 40°C
Lumens Delivered	(4000K) 9W: 1200lm 12W: 1800lm 16W: 2300lm
lm/W	(4000K) 9W: 135lm/W 12W: 145lm/W 16W: 145lm/W
CCT	3000/4000/6500K
UGR	26
Beam Angle	110

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without	0.875 kg
Packaging	
Colour / Finish	White
Diameter	325 mm
Height	85 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.9

PRODUCT FEATURES

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- Compatible with XPRESS emergency and microwave sensors
- High efficiency up to 145lm/W
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire

ACCESSORIES

ADIS2BZ/CH/2	Disco Evo 2 XPRESS Chrome Bezel
ADIS2BZ/BK/2	Disco Evo 2 XPRESS Black Bezel
ADIS2BZ/SC/2	Disco Evo 2 XPRESS Satin Chrome Bezel
ADIS2BZ/BB/2	Disco Evo 2 XPRESS Brushed Brass Bezel
AXPC/1/3NM	XPRESS Compact Emergency Kit
AXPC/1/3NM/DA	XPRESS Compact DALI Emergency Kit
AXPC/CF/1	XPRESS Compact Clip-In Microwave sensor with Corridor Function





Disco EVO

Part of the Bulkheads product category



Model	Disco EVO 2 XPRESS
Code	ADIS2/2
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Residential, Retail

