



Galaxy



Part of the Downlights product category

Model	Galaxy CCT Downlight
Code	AGAL/1
Application	Ancillary, Commercial, Healthcare

GENERAL INFORMATION

Input	220-240V
Wattage	11W - 16W
Operating Temp	-20°C - 35°C
Lumens Delivered	1600lm - 2300lm (4000K)
lm/W	140lm/W (4000K)
CCT	3000/4000/6000K
UGR	26
Beam Angle	110

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.68 kg
Colour / Finish	White
Diameter	226 mm
Height	70 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.95
L70 @ 25°C	L70 100,000h

PRODUCT FEATURES

- Multi-wattage compact IP65 LED performance downlight suitable for education, commercial and healthcare applications
- CCT selectable between 3000K, 4000K and 6000K and power selectable
- Low UGR Anti-Glare Design
- 210mm ceiling cut-out
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities

ACCESSORIES

AGPL/DG1/W	Galaxy CCT Trim Bezel c/w Drop Glass 1
AGPL/DG3/W	Galaxy CCT Trim Bezel c/w Drop Glass 3





Galaxy



Part of the Downlights product category

Model	Galaxy CCT Downlight
Code	AGAL/1
Application	Ancillary, Commercial, Healthcare

