

CAST Red Manual Call Point, Universal Mounting

Part No. **CA470**



Overview

- A high-quality red manual call point for use with C-TEC's XFP & ZFP 'CAST' protocol Addressable Fire Panels.
- LPCB certified to EN54 Parts 11 & 17 and Kiwa Telefication & DBI certified to EN54-13.
- Also certified to the relevant parts of EN54 with Swedish certification body SBSC.
- Surface or flush mountable.
- Onboard short-circuit loop isolator.
- Smooth-action resettable element mimics the feel of breaking glass.
- Supplied with reset/back box removal key and 'Not in Use' label.
- Red LED 'alarm ring' illuminates call point face upon activation.
- Photoluminescent operating window remains visible for up to 5 minutes.
- 5mA typical alarm current (370µA typical quiescent @ 22-40V DC).
- IP42 rated (IP67 rated version also available, order code CA47067)
- Yellow, green, blue and white versions also available.



More Information

'CAST' is the world's most-advanced 'distributed intelligence' fire alarm system protocol. Conceived, designed and realised by C-TEC as part of a five-year, multi-million pound project, it involved the creation of a powerful proprietary communication protocol (C-TEC Addressable System Technology, CAST) and multiple control panels & field devices. Now available to purchase, its key features include: • 255 devices per loop. • Autonomous decision-making for faster response times. • Multiple type codes. • 40V loop drive voltage. • Two 'soft' addressing options – automatic via the panel or manual via a powerful handheld programmer. • Powerful multi-level addressing facilitates easy device addition and swapped device identification. • Multiple functionality at a single address (integrated devices) • Volumes, tones & detector modes can be



T 01942 322744 E sales@c-tec.co.uk

F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



changed at compatible panels. • High-speed data transmission and robust data transfer. • Intrinsically EN54-13 compliant. • Provides geographical location of short and open circuit faults (a short circuit isolator is included as standard in every CAST field device). • Replace device function. • Future seamless integration with other CAST life safety systems reducing energy, servicing, installation and repair costs. • Designed and manufactured in the UK.

Technical Specifications

Approvals/certifications	Certified by SBSC to the relevant parts of EN54, DBI certified to EN54-13, LPCB certified to EN54 Parts 11 & 17 and Kiwa Telefication certified to EN54-13
Compatibility	Compatible with C-TEC's XFP/ZFP CAST Protocol Addressable Fire Panels.
Application/operation	Surface or flush mountable (supplied with a surface back box and flush mount adaptor plate for use in either application).
Supply/operating voltage	22 to 40V DC.
Quiescent current	370µA typical @ 22 to 40V DC.
Alarm current	5mA typical @ 22 to 40V DC.
Indicators	Red 'alarm ring'. Lit steady red (when activated) and flashing Red (when polling)
Connections	Loop IN, Loop OUT (x2).
Product dimensions (mm)	87 W x 88 H x D 62mm (includes back box).
Construction & finish	Red ABS polycarbonate; Glass fibre window.
IP Rating	IP42.
Weight	180g.
Operating conditions/temperature	-10°C to +55°C.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom