Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

Model identifier: 216672

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	Terminal					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

Flouder parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
0,	nption in on- 100 h), rounded st integer	40	Energy efficiency class	E		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	4 950 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500		
On-mode p expressed in W	oower (P _{on}),	40,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer dimensions without	Height	595	Spectral power	See image		
	Width	595	distribution in the	in last page		
	Depth	13		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	lf yes, equivalent power (W)	-			
		Chromaticity	0,313			
		coordinates (x and y)	0,337			
Parameters for LED and OLED light sources:						
R9 colour rendering index value 14		Survival factor	1,00			
the lumen maintenance factor	0,96					
(a)		I				

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

