

**Technical Specification** 

**Product Code: MAGDUO8** 

8 Zone 2-Wire Fire Alarm Panel **Description:** 





## **General Information**

Dimensions (mm)	331 x 331 x 99	
Materials	V0 rated ABS	
Maximum Detectors Per Zone	Up to 32 Devices (Dependant on Device Loading Units, 160 per Zone)	
Sounders and Detectors Mixed on Zones	Yes	
Maximum Cable Length Per Zone (m)	500	
Weight (Kg)	2.36	
Warranty (Years)	3	
Supply & Power		
Supply Voltage (V AC)	230 (Nominal 700mA)	
Operating Voltage (V DC)	21 -31	
Nominal Operating Voltage (V DC)	24	
Nominal Operating Current (mA)	700	
Maximum Cable Size (mm²)	1.5 (2 Core Screened Fire Rated Cable)	
Standby Supply	2 x 12V 3.2 Ah SLA Battery (Sold Seperately)	
PSU Output (4 Hour Continuous)(A)	2.1	
Inputs & Outputs		
Programmable Inputs	2; 3.3 Volts @ 10mA (Un-Monitored)	
Monitored Inputs	1; 3.3 Volts @ 10mA	
Zones	8; Up to 32 Devices (Dependant on Device Loading Units , 160 per Zone)	
Maximum Devices Per Zone	Up to 32 Devices (Dependant on Device Loading Units, 160 per Zone)	
Auxiliary Output	24V DC @ 250mA	
Output Zones	2 (Up to 32 Devices (Dependant on Device Loading Units , 160 per Zone))	
Monitored Outputs		
	Rated at 28V DC @ 200mA each	
Unmonitored Outputs		
	Fire & fault; 30V DC @ 1A each	
•	Rated at 28VDC @ 200mA each	
2 Un-Monitored Outputs	Fire & fault; 30VDC @ 1A each	

## **Environment**

Ingress Protection	IP30
Operating Temperature (°C)	+5 to +40

Supplied 2 x Battery leads (1 x Red, 1 x Black), 1 x Battery connecting Lead, 1 x 315mA quickblow fuse, 2 x panel keys, 2 x 680 Ohm resistor, 2 x 10K ohm Resistor, 2 x 3.275K Ohm Resistors

Standards BS EN 54-2, BS EN 54-4

Accessories **Features** 

BAT32: 12V 3.2Ah SLA Battery MAGDUOPK: 2 MAGDUO Panel Keys MAGDUOPCPS: MAGDUO Software

MAGDUOBBB: Battery Expansion Box for MAGDUO

Can be expanded to 12 Zones with MAGDUOZC4 or MAGDUOCC4



