Xnightsbridge


DATASHEET



BATM6

230V 6ft 38W Modular LED Batten - 4000K

www.mlaccessories.co.uk



MLA PART CODE	BATM6
DESCRIPTION	230V 6ft 38W Modular LED Batten - 4000K
NET WEIGHT (KG)	1.8
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1790 Height - 70 Width - 61
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
IK RATING	IK08
WATTAGE (W)	38
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	5250
LUMENS LIGHT SOURCE ONLY (LM)	5750
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	151
CIRCUIT WATTAGE (W)	38
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
RUNNING CURRENT (A)	0.17
DISPLACEMENT FACTOR	>0.7
SVM	0
PST-LM	0.01
BEAM ANGLE (DEGREES)	125
L70B50 LIFESPAN (HRS)	100000





Xnightsbridge

DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 54-114V OUTPUT CURRENT - 350mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 91.5 AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 85°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270852622

Date Created: 15/10/2024 14:42





