


DATASHEET



CYRAG

CyroLED Anti-Glare - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT (No Bezel)

www.mlaccessories.co.uk



MLA PART CODE	CYRAG
DESCRIPTION	CyroLED Anti-Glare - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT (No Bezel)
NET WEIGHT (KG)	0.198
DIFFUSER	Prismatic
DIMENSIONS (MM)	Diameter - 86 Height - 58 Projection - 5 Recessed Depth - 53 Minimum Void - 56
CUT-OUT (MM)	Cut-out Diameter - 70
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	4/6
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	350/395/405/395/480/580/585/545
LUMENS LIGHT SOURCE ONLY (LM)	730
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	120
CIRCUIT WATTAGE (W)	6.10
CCT	3000/4000/5000/6500K
LIGHT COLOUR	CCT
CRI	>90
SDCM	<6
RUNNING CURRENT (A)	0.029
DISPLACEMENT FACTOR	>0.7
SVM	0.016
PST-LM	0.144

BEAM ANGLE (DEGREES)	45
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	Yes*
FIRE-RATED	Tested to 30/60/90 minutes
I-JOIST RATED	30/90mins
WEB-JOIST RATED	30 minutes
IC RATED	Yes
ACOUSTIC RATED	Yes
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
DRIVER	EFFICIENCY FULL LOAD - 81
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5061061274934

Date Created: 20/06/2025 10:15

