


DATASHEET



HEX5

HELIX ONE 5FT 230V IP66 IK10 26W Modular Non-Corrosive Fitting - 4000K

www.mlaccessories.co.uk



MLA PART CODE	HEX5
DESCRIPTION	HELIX ONE 5FT 230V IP66 IK10 26W Modular Non-Corrosive Fitting - 4000K
NET WEIGHT (KG)	1.85
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1565 Height - 81 Width - 95 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK10
WATTAGE (W)	26
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3805
LUMENS LIGHT SOURCE ONLY (LM)	4425
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	167
CIRCUIT WATTAGE (W)	26.42
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.127
SVM	0.067
PST-LM	0.006
BEAM ANGLE (DEGREES)	115
L70B50 LIFESPAN (HRS)	70,000

LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT2
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270892086

Date Created: 07/05/2026 17:17

