Knightsbridge

DATASHEET




SL30CCTB

110-230V IP65 Triple Head Black 30W Security

Floodlight with PIR, Sensor, CCT and Manual Override

www.mlaccessories.co.uk



| MLA PART CODE | SL30CCTB |
|-------------------------------|--|
| DESCRIPTION | 110-230V IP65 Triple Head Black 30W Security Floodlight with PIR, Sensor,CCT and Manual Override |
| NET WEIGHT (KG) | 0.602 |
| FINISH | Black |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Width - 222 Projection - 190 Base Diameter - 107 Base Depth - 63 |
| TILT (DEGREES) | 270 |
| ROTATION (DEGREES) | 350 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | II |
| IP RATING | IP65 |
| WATTAGE (W) | 30 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 2675 |
| LUMENS LIGHT SOURCE ONLY (LM) | 2675 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 94.8 |
| CIRCUIT WATTAGE (W) | 28.2 |
| ССТ | 3000/4000/5500K |
| LIGHT COLOUR | ССТ |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.13 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.83 |





Xnightsbridge

| PST-LM | 0.14 |
|--|---------------|
| BEAM ANGLE (DEGREES) | 75 |
| LIFE SPAN (HRS) | 50,000 |
| L70B50 LIFESPAN (HRS) | 54,000 |
| DIMMABLE | No |
| OPERATING TEMPERATURE | -20~40°C |
| INPUT VOLTAGE | 110/230V |
| CABLE GLAND INCLUDED | Blind grommet |
| SENSOR TYPE | PIR |
| SENSOR OVERRIDE | Yes |
| SENSOR DETECTION ANGLE (DEGREES) | 90 |
| OPTIMUM DETECTION RANGE (M) | 8 |
| SENSOR DURATION | 2s - 10min |
| SENSOR LUX SETTINGS | 10lux-300lux |
| STANDBY POWER | <0.5W |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270864458 |

Date Created: 18/11/2024 11:08





